

**TECPINT CAL ECOLOGIC**

Highly breathable ecological lime paint

DESCRIPTION

Ecological wall paint with a matt mineral finish, pleasant texture and outstanding whiteness. Made from lime, calcium carbonates, talc and natural binders with inorganic pigments. Suitable for both interior and exterior surfaces. Highly breathable with excellent water vapour permeability.

USES

Lime-based paint designed for interior applications, ideal as a natural finish on rough or smooth plaster surfaces, whether new or previously painted, for both indoor and outdoor use. Particularly suitable for the restoration of historic buildings and monuments. Refreshes and enhances any interior or exterior surface previously coated with conventional paints where high breathability is required.

PROPERTIES

High alkalinity helps prevent the growth of fungi and microorganisms

Highly breathable

Excellent adhesion to building materials and existing paint coatings

Absorbs CO₂ during the curing process

High coverage rate

High whiteness level

Excellent water vapour permeability

VOC-free

Natural product that helps keep walls mould-free

Good abrasion resistance

Water dilutable

Easy to apply

TECHNICAL DATA

Thinner: Water

Finish: Matt

Colour: White

Specific gravity: 1.6 ± 0.05

Solids content: $64 \pm 4\%$

Drying time: 4–6 hours

Recoat time: 6–8 hours

Washability: Class 2

Adhesion: Excellent

Coverage: 3–5 m²/kg in 2 coats

**APPLICATION**

Surface preparation:

The surface must be sound, dry and free from dust and grease. Completely remove any loose or poorly adhered paint, efflorescence and any other substances that may affect adhesion.

Application method:

Stir the contents thoroughly until the product is completely homogeneous. Apply the first coat diluted with 5–10% water. Apply the second coat without dilution. Clean tools with water immediately after use. Apply at temperatures between 5 °C and 35 °C.

**Tecno Prodist**

TECNOLOGÍA EN QUÍMICA PARA CONSTRUCCIÓN Y MANTENIMIENTO