



TECNOSTOP CAIDAS

Anti-slip treatment for floors and bathtubs

APPLICATION:

The product reacts with the silicates on the surface, creating millions of microscopic anchoring points. The treatment is absorbed by the surface, providing long-lasting anti-slip protection. It is suitable for crystallised and low-porosity surfaces such as:

- Glazed ceramic
- Granite
- Vitrified coating
- Silestone
- Tiles, mosaics
- Polished concrete
- Terrazzo
- Shower trays and bathtubs

METHOD OF USE:

It is recommended to carry out a preliminary test to adjust the reaction time to existing conditions.

Wet the surface using a sponge, wearing gloves during application.

Leave the product on for the time estimated during the initial test, usually around 5 minutes .

Rinse thoroughly with water.

Apply the product in areas of 10–20 m² .

Approximate coverage: 10 m² per litre .

SAFETY PRECAUTIONS:

Treated surfaces may stain more easily over time due to the anti-slip effect.

Do not ingest. Keep out of reach of children.

Avoid contact with eyes, skin and mucous membranes.

Use appropriate gloves during application.

REGULATIONS:

Regulation (EC) No. 255/2003 : Legislative, regulatory and administrative provisions of Member States relating to the classification, packaging and labelling of HAZARDOUS MIXTURES.

Order 3/3/1980 concerning officially protected housing.

Royal Decree 486/1997 on occupational health and safety.

