



RESIPRO PLUS QUARTZ

BONDING BRIDGE RESIN, LIQUID ADHESIVE WITH QUARTZ FOR CONCRETES, MORTARS, PLASTERS, WOOD, METAL, ETC

description

Product based on acrylic resin with specially selected quartz aggregate and formulated as an adhesion primer prior to the placement of all types of mortars or plasters, favoring the anchoring of the same to the support.

PROPERTIES

- Direct application to pavement, tile, concrete, iron, galvanized, woods agglomerates, plywood and metal structures.
- Mechanical adhesion primer base quartz.
- Suitable for iron, with antioxidant.
- Without solvents.
- Non-flammable.
- Excellent adhesion on non-porous surfaces.
- Resistant to alkalinity.
- Resists high and low temperatures. -
- High density, does not hang up.
- Once dry, it contains very low water absorption (7% after 24 h. submerged).
- Applicable both outdoors and indoors on vertical and horizontal surfaces.

Features TECHNIQUES

Color:	Green
Appearance:	Granular viscous gel.
Density:	1.32 Kg./Ltr.
Solids content:	77%.
Performance:	7 - 10 m ² /L. and hand (according to absorption of the support).
Drying:	From 1 to 2 hours depending on the ambient temperature and humidity. Water vapor breathability V2.
Brooksiel:	-35 rpm. 200-1500
Implementation:	Brush, roller

HOW TO USE

The supports must be healthy, solid, dry, clean and free of dust, grease and products release agents, grouts or weakly adhered materials. Your best results they are achieved on smooth supports or with little surface absorption (concrete, brick, etc.).

The product is supplied ready for use, but it must be homogenized before commissioning.

It can be diluted for absorbent surfaces or for spray application to a maximum of 20%.

Do not apply the product at temperatures below 5°C or above 35°C.

The tools should be cleaned with water immediately after use, before the product has hardened.

Do not apply on wet or waterlogged substrates.

Store in a dry place, in its original container, tightly closed and sheltered from moisture.

PACKAGING

750 ml. / 4 L. / 14L.

INFORMATION ADDITIONAL

Its use is intended as an adhesion layer, for application on supports little absorbents, and for the subsequent realization of mortars of all kinds, both normal as a waterproof, lime-based, cement or plaster. It can be applied above all type of materials commonly used in construction, whether outdoors as indoors and on vertical and horizontal surfaces.

Our Technical Service is at your disposal to expand the information contained in this sheet and to advise you on systems, processes and more the suitable products, according to the surfaces, environments and needs that you want to cover. With this technical sheet we only try to inform and advise according to our criteria and experience, not being able to take responsibility for the consequences from the use of these products beyond our control, the conditions and circumstances of their application.



Tecno Produst[®]

Chemical solutions for construction and maintenance